

Date 2024-12-13

Anchorage and use of anchor inside port

- **Anchorage areas:**
 - Karlshamn inner (A) N56 06.9 E014 51.3
 - Karlshamn (C) N56 04.4 E014 47.5
- **Unsuitable areas:**
 - Close to fairway line
- **Prohibited areas:**
 - Safety distance minimum 1000m to underwater cables at Anchorage (A)
- **Use of anchor inside port:**
 - No limitations

Berth information and maximum dimensions

Elleholm								
Berth	Cargo	Direction	Length (m)	Max Loa (m)	Max Boa (m)	Depth (m) acc. MVY	Max draft (m)	Remarks
1	Split stone	005 ⁰ /185 ⁰	63m	110m	16,5m	6,4m	5,6m	Working bowthruster required for vessels LOA>82m.

Tugboat information and requirements

- Tugboat normally not applicable
- *If a tugboat is used, visibility must be at least 200 m*
- **Escort tug requirements**
 - N/A
- **Bollard pull/Safe working load requirements - SWL (bollards and fairleads)**
 - No specific requirements, but vessel to have sufficient SWL for the current operation concerning weather and loading conditions
- **Local tugboat requirements**
 - Tugboat normally not applicable

Date 2024-12-13

Visibility restrictions

- Normally not applicable
- *If a tugboat is used, visibility must be at least 200 m*

Daylight restrictions

- Normally not applicable

Wind restrictions

- All vessels Max 10 m/s wind from W-S-E

Source: According to SMHI/Bizmet

Wave and swell restrictions

- Normally not applicable

Current restrictions

- Normally not applicable

Two man pilotage

- Normally not applicable

Ice restrictions

- According to www.sjofartsverket.se/winternavigation.

Other restrictions

- Normally not applicable.